

TRIPLE TRACK PATIO ORDER FORM Fax Back To: 01656 746 786 / 744 138 To avoid any delay on your order please supply all relevant details.

Company:		Contact:	Custo	mer Ret:		
Address:			Tel:		Fax:	
			Mob:		Email:	
Post Code:		Date Req:		No:	Page:	of:
Quotation 🔲 O	rder 🔲 Glazeo			ery Collecti	on 🔲	
CONFIGURATIONS (ALL VIEWED EXTERNALLY) Please depict style required using directional arrows or 'F' for fixed.						
			g p			
2 Pane 3 Pane 4 Pane 6 Pane						
Size:	Overall Frame Widtl	າ (inc Add On):		Outer Frame Height	(inc Add On):	
	Glass:			Stain / Pattern:		
Glass:	Spacer: Ali	W/Edge Lead	: 6mm 9mm	Georgian Bar:	Other Details:	
Frame Colour:	White	(Golden Oak 🔲		G/Oak on White	
	Rosewood _	F	Rosewood on White		Anth Grey on White	
	Smooth Anth Grey o	n White 🔲	Smooth Slate Grey on White			
	All Colours Below A	Are On An Extended Lo	ead Time - 8 / 10 Weeks Fr	om Point of Order		
	Whitegrain on White	· 🔲	Whitegrain Both Sides		Anthracite Grey Both Sides	; 🔲
	Black Brown	E	Black Brown on White		Smooth Anthracite Both Si	des 🔲
	Cream on White		Cream Both Sides 🔲		Smooth Slate Grey Both Si	des 🔲
	Special Order / Othe	er Colours:				
Outer Frame:	Welded	Mechanically Jointed	(supplied in kit form)			
Cill:	None 150mm 180mm (Please see note sections 7 & 8 for more information.)					
Drainage:	Hidden 🔲	Face	None			
Hardware Colour:	White	Polished Gold	Graphite	Chrome	Black 🔲	Anthracite Grey
Trickle Vent:	No 🔲	Yes (4000mm Airflow in	40mm Add On only)			
Add On:	No 🔲	40mm 🔲	Left	Right	Head 🔲	
1: Trickle vents, 4000mm only, fitted to 40mm add-on. 2: Unglazed frames supplied to take 28mm sealed units / panels. 3: 36mm Unit Depth Maximum. 4: Maximumum unit weight 80kg, maximum over all sash weight 100kg. 5: Please note no mid rails available, as a result you cannot have a letterplate. 6: Standard outer frame depth 85mm, Triple track outer frame depth 160mm 7: Cill sections on the triple track as follows: 150mm sits 10mm behind edge of outerframe, 180mm sits 20mm in front of the edge of the outerframe. 8: It is recommended to use 2 x15mm add ons on the back of the threshold and 1 x cill at the front to achieve the desired projection. 9: No low threshold option available.						
Additional Details						
I confirm that the above design & measurements are my specified requirements. As such I am responsible for the information given. Please proceed with this order.			No of Items		Price (+ vat / inc vat):	
I understand that no changes can be now made without additional cost. Sun's terms and conditions of sale apply & the order is placed by me on that basis. I			Deposit Paid:		Balance on Del:	
understand quotes are valid for 30 days. Customers Signature: (unsigned orders will be returned)						